

TVS
EUROGRIP
OFF HIGHWAY TYRES

**MAXIMUM
PERFORMANCE
& RELIABILITY**



AR 600 - 700 - 800



AR 600



AR 700



AR 800



- Longitudinal high angle lugs with more rubber area in contact with ground for Excellent rolling behavior offering ride comfort and high stability during on road applications
- Optimum number of lugs & uniform footprint distribution for Effective self-cleaning properties for high traction performance in hard pull applications.
- Robust Construction provides excellent dimension stability with durable performance across product life cycle. Special Tread compound developed for ON & OFF-Road movement of modern tractors which ensures high wear-resistance as well as excellent traction.

AR600

SN	Size	Rim	SW	OD	SLR	RC	Tread Depth	LI
			(mm)	(mm)	(mm)	(mm)	(mm)	
1	320/65R16	W10	320	830	366	2440	33	117D
2	320/65R18	W10	319	873	392	2580	33	119D
3	340/65R18	W11	343	899	406	2670	34	122D
4	420/65R20	W13	418	1054	480	3190	38	135D
5	440/65R20	W14L	440	1080	490	3245	45	138D
6	420/65R24	W13	415	1156	578	3415	37	126D
7	440/65R24	W14L	432	1197	547	3529	45	135D
8	480/65R24	W15L	480	1238	557	3645	47	133D
9	540/65R24	DW 16L	540	1324	595	3737	50	140D
10								146D
11	440/65R28	W14L	435	1283	590	3765	44.5	131D
12							138D	
13	480/65R28	W15L	480	1355	614	4029	46	136D
14							142D	
15	540/65R28	W16L	535	1427	643	4205	49	142D
16	540/65R30	W16L	530	1474	668	4447	50	150D
17	540/65R34	W16L	520	1571	725	4614	49	145D
18								152D
19	540/65R38	W16L	515	1672	780	5137	49	153D
20	600/65R38	DW20B	585	1763	886	5277	54	153D
21								159D
22	650/65R38	DW20B	645	1834	847	5569	60	157D
23								171D

AR700

SN	Size	Rim	SW	OD	SLR	RC	Tread Depth	LI
			(mm)	(mm)	(mm)	(mm)	(mm)	
1	200/70R16	W6	197	686	314	2055	26	94D
2	240/70R16	W8	246	744	340	2258	27	104D
3	260/70R16	W8	256	772	370	2317	28	109D
4	280/70R16	W8L	274	800	360	2419	30	112D
5	280/70R18	W9	280	849	390	2580	30	114D
6	260/70R20	W8	258	872	400	2630	30	113D
7	280/70R20	W9	282	900	415	2720	32	116D
8	300/70R20	W9	300	955	435	2850	34	120D
9	320/70R20	W10	319	982	452	2931	32	123D
10	360/70R20	W11	360	1046	473	3079	42	129D
11	380/70R20	W12	380	1086	495	3250	45	132D
12	320/70R24	W10	310	1097	509	3343	40	116D
13	360/70R24	W11	355	1152	525	3400	41	122D
14	380/70R24	W12	385	1194	555	3480	42	125D
15	420/70R24	W13	425	1252	565	3630	45	130D
16	480/70R24	W15L	479	1316	591	3919	50	138D
17	320/70R28	W10	319	1192	555	3560	40.5	119D
18	360/70R28	W11	357	1251	580	3769	41	125D
19	380/70R28	W12	385	1295	597	3885	43	127D
20	420/70R28	W13	420	1350	609	3967	47	133D
21	480/70R28	W15L	485	1405	632	4138	50	140D
22	420/70R30	W13	418	1398	640	4160	47	134D
23	480/70R30	W15L	482	1480	668	4412	50	141D
24	520/70R30	W16L	516	1536	700	4500	55	145D
25	480/70R34	W15L	485	1580	723	4760	50	143D
26								149D
27								155D
28	520/70R34	W16L	516	1640	743	4890	53	148D
29								168D
30	480/70R38	W15L	479	1681	778	5060	50	145D
31	520/70R38	W16L	520	1750	798	5194	53	150D
32	580/70R38	W18L	580	1810	811	5308	57	155D
33								180D (SB)
34	580/70R42	W18L	577	1879	850	5570	58	158D
35	620/70R46*	DW20B	625	2036	924	6106	58	162D

AR 800 - 80 series

SN	Size	Rim	SW	OD	SLR	RC	Tread Depth	LI
			(mm)	(mm)	(mm)	(mm)	(mm)	
1	480/80R42	DW16L	494	1835	843	5430	50	151D
2								166D*
3								173D*
4	480/80R46	DW16L	494	1960	905	5861	50	158D
5								166D*
6								173D*
7	480/80R50	DW16L	480	2050	939	6072	54	159D
8								166D*
9								173D*

AR 800 - 85 Series

SN	Size	Rim	SW	OD	SLR	RC	Tread Depth	LI
			(mm)	(mm)	(mm)	(mm)	(mm)	
1	250/85R20	W8	250	940	426	2810	37	116D
2	280/85R20	W10	292	984	439	2904	30	112D
3								122D
4	320/85R20	W11	333	1055	475	3118	41	119D
5	250/85R24	W8	250	1035	473	3040	39	109D
6	280/85R24	W10	305	1090	508	3280	40	115D
7	320/85R24	W11	335	1154	530	3398	43	122D
8	340/85R24	W12	358	1188	550	3543	45	125D
9	380/85R24	W12	385	1260	569	3717	45	131D
10	420/85R24	W15L	440	1328	604	3898	50	137D
11	250/85R28	W8	251	1137	529	3420	37	112D
12	280/85R28	W10	302	1192	551	3547	42.0	120D
13	320/85R28	W11	330	1260	575	3727	43	124D
14	340/85R28	W12	375	1293	585	3849	44	127D
15	380/85R28	W12	385	1360	622	4025	45	133D
16	420/85R28	W15L	447	1429	645	4236	47	139D
17	380/85R30	W12	380	1408	633	4138	45	135D
18	420/85R30	W15L	445	1488	675	4406	50	140D
19	460/85R30	DW15L	480	1545	685	4575	53	145D
20	320/85R34	W11	329	1408	664	4283	43.5	141D
21	380/85R34	W12	385	1510	692	4462	45	137D
22	420/85R34	W15L	440	1580	727	4773	50	142D
23	460/85R34	DW15L	483	1651	770	4997	53	147D
24								157D
25	340/85R36	W12	353	1492	684	4433	44.5	132D
26	340/85R38	W12	355	1546	726	4704	46	133D
27								151D
28	420/85R38	W15L	440	1680	772	4950	50	144D
29	460/85R38	DW15L	483	1752	799	5222	57	149D
30								167D
31	520/85R38	DW16L	535	1850	841	5483	56	155D
32								169D
33	520/85R42	DW16L	540	1957	904	5858	56	157D
34								169D
35	520/85R46*	DW16L	520	2054	938	6126	56	164D


*Coming soon

FEATURES & BENEFITS



Excellent Rolling Behavior

Longitudinal high angle lugs & more rubber area in contact with road provide excellent rolling behavior




Pattern Design

Tread pattern design with improved footprint distribution for better soil compaction and traction




Cut + Chipping & Chunking Resistance

Tread compound formulated to give better wear and tear resistance



Comfort & Ride

The optimally spaced lugs, with thick nose bars and more rubber area in contact with road provide smooth performance on hard surface



Robust Construction

Polyester construction provides excellent dimension stability



Tie Bar @ Centre Circumferentially

Tie bars provide stability to lugs and helps reduction of lug shuffling

ABOUT TVS EUROGRIP

A foremost off-highway tyre manufacturer, part of TVS Mobility Group - one of India's largest auto ancillary conglomerates.

Have been manufacturing and exporting tyres to more than 85+ countries since the early 1990s.

Comprising a portfolio of over 1000+ products and expanding the range for markets worldwide.

Specializing in agriculture, construction, industrial and OTR segments.

World-class products with superior design and engineering.



85+
COUNTRIES



LEADING
TYRE BRAND



WORLD-CLASS
PROCESSES



CUSTOM
DEVELOPMENT

WORLD-CLASS R&D PRACTICES

SUSTAINABILITY & ENVIRONMENT PROTECTION



71% FROM
RENEWABLE ENERGY



ZERO EFFLUENT
DISCHARGE



Follow us on



tvseurogripohTTYRES



export@eurogriptyres.com

SCAN FOR MORE

